

Cheque Personalization Encoder / Printer

BP63S

Tape Dispenser



On – Demand Cheque Book Production The unique solution

New BP63S Cheque and Document printer encode and print Cheques and Giro.
BP63S is a perfect printer for Banks, Financial Institutions, Security Management, wherever high quality and security printing is required.

For the purpose of security only Impact MICR printing is used.

BP63S takes maximum advantages of the available technology providing a powerful production environment for pre-encoding and personalisation of cheques or value documents.

ADVANTAGES:

Easy to maintain and service
Low noise
Flash Programmable
Label dispenser
Staple up to 50 cheques + cover

Cheque Printing Software included.
Security with passwords
Unlimited queue list, with VIP transfer
2 document types

Software options:
5, 10 or 20 document types
Full report system (Audit Trail)
Backup feature

BP63S

Specifications		
Model	DR85U	OICR & Personalization encoder with Inkjet printer
Document Feeder	Type	Auto Feeder
	Capacity	700 documents (with 0.116 mm document)
MICR Encoder	Font	E13B or CMC7 (factory option)
	Encoding fields	All fields (Max 65 columns)
	MICR ribbon type	Cassette one-time ribbon (65,000 characters/cassette)
Inkjet Printer (Manual adjustment)	Number of printing character	Total 622 characters (322 characters/line x 4 lines)
	Printing character font	Numeric, Alphabet capital, Symbol Rt k p v 372J , 3922Y ' f q v d k o c r ' l o c i g
	Vertical printing position	39 - 339 mm from bottom q h f q e ' O c p w c i c f l w u r g f
	J q t k q p x n	5/4: 2 o o ' h t q o ' t k i j v ' g f i g ' q ' r g u v ' q h ' f q e w o g p v 0
Output Stacker	Capacity	700 documents (with 0.116 mm document)
Stapler Label dispenser	5000 staple	"YES
	250 label's	"YES
Document Specification	Length	152-2: 0 mm
	Height	85-110 mm
	Thickness	0.096-0.116 mm
Processing speed		70 documents/min (encoding 40 MICR characters + personalisation data with inkjet printing)
Dimension	BP63S	3342Y , 632F , 462J " o o
Weight		4: kg
Power Supply		100-240V(10%), 50/60Hz, 110VA
Communication Interface		USB1

Arctic Heating AS
Smidsrødveien 95,
N-3120 Nøtterøy - NORWAY

Telephone +47 33 30 42 20
Fax +47 33 32 29 02
Electronic mail: arctic@heating.no
Homepage: www.arctic-heating.com